

Air Grinder & Wire Brush



ST-7580L 5" Speed: 7,600 rpm
ST-7680L 6" Speed: 6,300 rpm
Straight Grinder(Lever Type)
W/O Grinder Wheel



ST-7580 5" Speed: 7,600 rpm
ST-7680 6" Speed: 6,300 rpm
Straight Grinder(Roll Type)
W/O Grinder Wheel



ST-7580LH 5" Speed: 7,600 rpm
ST-7680LH 6" Speed: 6,300 rpm
Straight Grinder(Lever Type)
W/Hose & W/O Grinder Wheel



ST-7580H 5" Speed: 7,600 rpm
ST-7680H 6" Speed: 6,300 rpm
Straight Grinder(Roll Type)
W/Hose & W/O Grinder Wheel



ST-7780L
3" Straight Grinder (Lever Type)
(W/O Grinder Wheel)
Speed: 12,000 rpm



ST-7780
3" Straight Grinder (Roll Type)
(W/O Grinder Wheel)
Speed: 12,000 rpm

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Throttle Type	Grinding Wheel		Free Speed	Spindle Size ϕ	Overall Length		Weight (lb)	Air Hose I.D. (in.)	Air Inlet NPT (in.)	Hp	Max. Air Consumption (cfm)
		mm	in			mm	in					
ST-7580L	Lever	125 x 19 x 12.7	5 x 3/4 x 1/2	7,600	1/2 x 12	501	19-11/16	2.97	12.7	3/8	1.3	20
ST-7580LH	Lever	125 x 19 x 12.7	5 x 3/4 x 1/2	7,600	1/2 x 12	501	19-11/16	2.97	12.7	3/8	1.3	20
ST-7680L	Lever	150 x 25 x 15.8	6 x 1 x 5/8	6,300	5/8 x 11	521	20-33/64	4.14	12.7	3/8	1.3	24
ST-7680LH	Lever	150 x 25 x 15.8	6 x 1 x 5/8	6,300	5/8 x 11	521	20-33/64	4.14	12.7	3/8	1.3	24
ST-7580	Roll	125 x 19 x 12.7	5 x 3/4 x 1/2	7,600	1/2 x 12	400	15-3/4	2.97	12.7	3/8	1.3	20
ST-7580H	Roll	125 x 19 x 12.7	5 x 3/4 x 1/2	7,600	1/2 x 12	400	15-3/4	2.97	12.7	3/8	1.3	20
ST-7680	Roll	150 x 25 x 15.8	6 x 1 x 5/8	6,300	5/8 x 11	425	16-47/64	4.14	12.7	3/8	1.3	24
ST-7680H	Roll	150 x 25 x 15.8	6 x 1 x 5/8	6,300	5/8 x 11	425	16-47/64	4.14	12.7	3/8	1.3	24

Model No.	Max. Free Speed (rpm)	Wheel Size ϕ (mm)	Spindle Size ϕ	Weight (lb)	Length (in.)	Air Hose I.D. (in.)	Air Inlet NPT (in.)	Avg. Air Consumption (cfm)	Packing Pcs/Ctn/G.W./Cuft (kgs)
ST-7780L	12,000	75 x 9.5 x 13	3/8"-24 UNF	4.4	16-3/4	3/8"	1/4"	24	6pcs/Ctn/17/1.8'
ST-7780	12,000	75 x 9.5 x 13	3/8"-24 UNF	5.0	15	3/8"	1/4"	24	6pcs/Ctn/17/1.8'



Air Grinder

◆ Disc is not included.



ST-7744G 4" - Speed: 13,600 rpm
ST-7745G 5" - Speed: 10,900 rpm
ST-7747G 7" - Speed: 7,600 rpm
 Industrial Air Grinder (Roll Type)



ST-7744L 4" - Speed: 13,600 rpm
ST-7745L 5" - Speed: 10,900 rpm
ST-7747L 7" - Speed: 7,600 rpm
 Industrial Air Grinder (Lever Type)

For **ST-7744G(L)**
ST-7745G(L)
ST-7747G(L)

"B" Type

4" & 5" Grinder - 3/8"-24 spindle
 5" & 7" Grinder - 5/8"-11 spindle

"C" Type

4" & 5" Grinder - 8mmx1.25mm spindle
 7" Grinder - 10mmx1.5mm spindle



ST-7741
 7" Angle Grinder (Lever Type)
 Speed: 7,000 rpm



ST-7779
 7" Angle Grinder (Roll Type)
 Speed: 7,000 rpm



Lever Type

ST-7779L
 7" Angle Grinder (Lever Type)
 Speed: 7,000 rpm



ST-7783
 7" Heavy Duty Vertical Grinder
 Speed: 7,000 rpm
 Spindle: 5/8"-11



ST-7784
 9" Heavy Duty Vertical Grinder
 Speed: 5,900 rpm
 Spindle: 5/8"-11



ST-7789
 9" Industrial Vertical Grinder (Side Exhaust)
 Speed: 6,500 rpm
 Spindle: M16x2.0

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Capacity		Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		in	mm	in	mm			cfm	l/min	Lbs	kgs	
ST-7744G	13,600	4	100	8-3/16	208	1/4"	3/8"	19	540	3.3	1.5	10Pcs/Ctn/25/2.37'
ST-7745G	10,900	5	125	8-3/16	208	1/4"	3/8"	19	540	3.5	1.6	10Pcs/Ctn/26/2.37'
ST-7747G	7,600	7	180	10	254	3/8"	1/2"	29	820	6.8	3.1	6Pcs/Ctn/27/3.13'
ST-7744L	13,600	4	100	8-3/16	208	1/4"	3/8"	19	540	3.3	1.5	10Pcs/Ctn/25/2.37'
ST-7745L	10,900	5	125	8-3/16	208	1/4"	3/8"	19	540	3.5	1.6	10Pcs/Ctn/26/2.37'
ST-7747L	7,600	7	180	10	254	3/8"	1/2"	29	820	6.8	3.1	6Pcs/Ctn/27/3.13'
ST-7741	7,000	7	180	13-1/2	343	3/8"	1/2"	29	820	7.0	3.2	6Pcs/Ctn/20/2.32'
ST-7779	7,000	7	180	13-1/8	333	3/8"	3/8"	29	820	6.93	3.15	6Pcs/Ctn/22/1.8'
ST-7779L	7,000	7	180	13-1/2	343	3/8"	3/8"	29	820	7.04	3.2	6Pcs/Ctn/23/2.0'
ST-7783	7,000	7	180	7-1/2	185	1/2"	3/8"	29	820	9.7	4.4	4Pcs/Ctn/21/2.1'
ST-7784	5,900	9	230	10-63/64	279	1/2"	3/4"	40	1130	12.87	5.8	4Pcs/Ctn/24.5/2.9'
ST-7789	6,500	9	230	12-3/5	320	1/2"	3/4"	40	1130	12.56	5.7	4Pcs/Ctn/26.5/2.32'



Air Grinder

◆ Disc is not included.



ST-7841
4" Reversible Cutter and Grinder
Speed: 12,000 rpm



ST-7841L
4" Extended Reversible Air Cutter
Speed: 15,000 rpm



ST-7841SA
4" Reversible Air Grinder
Speed: 13,000 rpm

NEW



ST-7841SL
4" Extended Reversible Air Cutter
Speed: 15,000 rpm

NEW

ST-7841SB
4" Reversible Air Cutter
Speed: 15,000 rpm



ST-7736 4"
ST-7737 5"
Angle Grinder (Lever Type)
Speed: 11,000 rpm



ST-7843 4"
ST-7842 5"
Angle Grinder (Lever Type)
Speed: 11,000 rpm, Rear Exhaust



ST-7851 4"
ST-7852 4-1/2"
ST-7853 5"
Angle Grinder

NEW



ST-7736G 4"
ST-7737G 5"
Angle Grinder (Roll Type)
Speed: 11,000rpm



ST-77364G
4" Mini Angle Grinder
(Roll Type)
Speed: 13,000 rpm



ST-77364
4" Mini Angle Grinder
(Lever Type)
Speed: 13,000 rpm

Lever Type



ST-77365G 4"
ST-77365G-5 5"
Air Angle Grinder
(Roll Type)



ST-77365 4"
ST-77365-5 5"
Air Angle Grinder
(Lever Type)

Lever Type

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Size (in)	Air Inlet (PT)	Min. Hose Size		Air Consumption		Overall Length		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
				in	mm	cfm	l/min	in	mm	lbs	kgs	
ST-7841	12,000	4	1/4"	3/8	10	19	540	9.2	234	2.4	1.1	12/Ctn/19/1.5'
ST-7841L	15,000	4	1/4"	3/8	10	19	540	14.8	376	3.2	1.4	12/Ctn/21.5/2'
ST-7841SA	15,000	4	1/4"	3/8	10	19	540	14.8	376	2.4	1.1	12/Ctn/21.5 / 2'
ST-7841SB	13,000	4	1/4"	3/8	10	19	540	9.2	234	2.4	1.1	12/Ctn/19/2'
ST-7841SL	15,000	4	1/4"	3/8	10	19	540	9.2	234	2.4	1.1	12/Ctn/19/2'
ST-7736(G)	11,000	4	1/4"	3/8	10	19	540	9	230	4.0	1.8	10/Ctn/21/1.45'
ST-7737(G)	11,000	5	1/4"	3/8	10	19	540	9	230	4.0	1.8	10/Ctn/21/1.45'
ST-7843	11,000	4	1/4"	3/8	10	19	540	10.8	275	4.4	2.0	10/Ctn/21/1.45'
ST-7842	11,000	5	1/4"	3/8	10	19	540	10.8	275	4.4	2.0	10/Ctn/21/1.45'
ST-7851	11,000	4	1/4"	3/8	10	19	540	9.1	232	4.0	1.8	6/Ctn/13/1.8'
ST-7852	11,000	4-1/2	1/4"	3/8	10	19	540	9.1	232	4.0	1.8	6/Ctn/13/1.8'
ST-7853	11,000	5	1/4"	3/8	10	19	540	9.1	232	4.0	1.8	6/Ctn/13/1.8'
ST-77364(G)	13,000	4	1/4"	3/8	10	19	540	7.0	180	2.1	1.0	10/Ctn/12.6/1.5'
ST-77365(G)	12,000	4	1/4"	3/8	10	19	540	8.5	220	3.5	1.6	10/Ctn/16/1.8'
ST-77365(G)-5	12,000	5	1/4"	3/8	10	19	540	9.1	232	4.0	1.8	10/Ctn/16/1.8'



Industrial Air Angle Grinder

Features:

- ★ The cylinder is durable and longer lifespan.
- ★ Increase gear strength, consequently the abrasive life is improved.



Industrial

ST-7435 1/4"
ST-7435M 6mm
(Lever Type)
0.4HP



Industrial

ST-7435G 1/4"
ST-7435GM 6mm
(Rotary Type)
0.4HP



Industrial

ST-7435A 1/4"
ST-7435AM 6mm
(Lever Type)
0.4HP



Industrial

ST-7435AG 1/4"
ST-7435AGM 6mm
(Rotary Type)
0.4HP



Industrial

ST-7830L 2"
(Lever Type)
0.4HP



ST-7830G 2"
(Rotary Type)
0.4HP



ST-7834L 4"
(Lever Type)
0.7HP



ST-7834G 4"
(Rotary Type)
0.7HP



Industrial

ST-7844L 4"
ST-7845L 5"
(Lever Type)
1HP



ST-7844G 4"
ST-7845G 5"
(Rotary Type)
1HP



Industrial

ST-7871L-A 7"
spindle:5/8"x11UNF
ST-7871L-B 7"
spindle:1/2"x16
(Lever Type)
1.3HP



ST-7871G-A 7"
spindle:5/8"x11UNF
ST-7871G-B 7"
spindle:1/2"x16
(Rotary Type)
1.3HP



ST-7890L 9"
(Lever Type)
2.5HP



ST-7890G 9"
(Rotary Type)
2.5HP



ST-7436
3" Straight Grinder
(Lever Type)
0.9HP



ST-7436G
3" Straight Grinder
(Rotary Type)
0.9HP

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Disc Size (inch)	Spindle Size (Dia. x thread)	Air Inlet (PT)	Air Hose (I.D.)	Avg Air Consumption		Overall Length		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
						cfm	l/min	in	mm	lbs	kgs	
ST-7435(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.54	166	1.65	0.75	20Pcs/Ctn/18/0.9'
ST-7435G(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.26	159	1.41	0.64	20Pcs/Ctn/15/0.8'
ST-7435A(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.54	166	1.68	0.76	20Pcs/Ctn/18/0.9'
ST-7435AG(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.26	159	1.43	0.65	20Pcs/Ctn/15/0.8'
ST-7830L	15,000	2	1/4"-28UNF	1/4	3/8	13	380	6.61	168	1.68	0.76	20Pcs/Ctn/18/0.9'
ST-7830G	15,000	2	1/4"-28UNF	1/4	3/8	13	380	6.22	158	1.41	0.64	20Pcs/Ctn/15/0.8'
ST-7834L	15,000	4	M8x1.0	1/4	3/8	19	540	7.28	185	2.53	1.15	10Pcs/Ctn/13/1.1'
ST-7834G	15,000	4	M8x1.0	1/4	3/8	19	540	7.28	185	2.53	1.15	10Pcs/Ctn/13/1.1'
ST-7844L	13,500	4	M8x1.25	1/4	3/8	19	540	10.63	270	4.44	2.02	10Pcs/Ctn/19/1.5'
ST-7844G	13,500	4	M8x1.25	1/4	3/8	19	540	8.59	218	3.83	1.74	10Pcs/Ctn/19/1.3'
ST-7845L	13,500	5	M14x2.0	1/4	3/8	19	540	10.63	270	4.44	2.02	10Pcs/Ctn/21/1.5'
ST-7845G	13,500	5	M14x2.0	1/4	3/8	19	540	8.59	218	3.83	1.74	10Pcs/Ctn/19/1.3'
ST-7871L-A	7,000	7	5/8"-11UNF	3/8	3/8	29	820	10.71	272	5.59	2.54	6Pcs/Ctn/19/1.6'
ST-7871L-B	7,000	7	1/2"-16	3/8	3/8	29	820	10.75	273	5.28	2.4	6Pcs/Ctn/19/1.6'
ST-7871G-A	7,000	7	5/8"-11UNF	3/8	3/8	29	820	10.04	255	5.9	2.68	6Pcs/Ctn/19/1.6'
ST-7871G-B	7,000	7	1/2"-16	3/8	3/8	29	820	10.04	255	5.9	2.68	6Pcs/Ctn/19/1.6'
ST-7890L	5,900	9	1/2"-16	1/2	3/8	40	1130	13.78	350	9.68	4.4	4Pcs/Ctn/22/1.4'
ST-7890G	5,900	9	1/2"-16	1/2	3/8	40	1130	12.17	309	9.68	4.4	4Pcs/Ctn/22/1.4'
ST-7436	14,600	-	5/16"-24T	3/8	3/8	20	566	15.35	390	3.78	1.72	10Pcs/Ctn/15/0.6'
ST-7436G	14,600	-	5/16"-24T	3/8	3/8	20	566	13.58	345	2.86	1.3	10Pcs/Ctn/15/0.6'



Industrial Air Die Grinder



Industrial

ST-7434 1/8"
ST-7434M 3mm
Air Die Grinder
(Lever Type)
0.21HP



Industrial

ST-7434G 1/8"
ST-7434GM 3mm
Air Die Grinder
(Rotary Type)
0.21HP



Industrial

ST-7431 1/4"
ST-7431M 6mm
Air Die Grinder
(Lever Type)
0.45HP



Industrial

ST-7431G 1/4"
ST-7431GM 6mm
Air Die Grinder
(Rotary Type)
0.45HP



Industrial

ST-7432 1/4"
ST-7432M 6mm
Air Die Grinder
(Lever Type)
0.35HP



Industrial

ST-7432G 1/4"
ST-7432GM 6mm
Air Die Grinder
(Rotary Type)
0.35HP



Industrial

ST-7430 1/4"
ST-7430M 6mm
Air Die Grinder
(Front Exhaust) (Level type)
0.5HP



Industrial

ST-7769 1/4"
ST-7769M 6mm
Air Die Grinder
(Front Exhaust) (Level type)
0.4HP



Industrial

ST-7433 1/4"
ST-7433M 6mm
Extended Air Die Grinder
(Lever Type)
Magnesium Alum. Alloy
Alloy Housing
0.9HP



Industrial

ST-7433G 1/4"
ST-7433GM 6mm
Extended Air Die Grinder
(Rotary Type)
Magnesium Alum. Alloy
Alloy Housing
0.9HP



Industrial

ST-7432-4 1/4"
ST-7432M-4 6mm
4" Extension
Air Die Grinder
(Lever Type)
0.3HP



Industrial

ST-7432G-4 1/4"
ST-7432GM-4 6mm
4" Extension
Air Die Grinder
(Rotary Type)
0.3HP

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Collet		Motor (HP)	Free speed (r.p.m)	Weight		Length		Air Consumption		Air Inlet (PT) (in)	Air hose (I.D.) (in)	Packing Pcs/ctn/w.g./cuft (kgs)
	in	mm			Lb	kgs	in	mm	cfm	l/min			
ST-7434(M)	1/8	3	0.21	30,000	1.01	0.46	5.91	150	13	380	1/4	3/8	20Pcs/Ctn/12/0.8'
ST-7434G(M)	1/8	3	0.21	30,000	0.97	0.44	5.99	152	13	380	1/4	3/8	20Pcs/Ctn/12/0.8'
ST-7431(M)	1/4	6	0.45	18,000	1.76	0.80	6.97	177	13	380	1/4	3/8	20Pcs/Ctn/20/1'
ST-7431G(M)	1/4	6	0.45	18,000	1.81	0.82	7.20	183	13	380	1/4	3/8	20Pcs/Ctn/18/0.9'
ST-7432(M)	1/4	6	0.35	24,000	1.5	0.68	6.61	168	13	380	1/4	3/8	20Pcs/Ctn/15/0.9'
ST-7432G(M)	1/4	6	0.35	24,000	1.36	0.62	6.81	173	13	380	1/4	3/8	20Pcs/Ctn/15/0.9'
ST-7430(M)	1/4	6	0.5	25,000	1.85	0.84	6.1	156	13	380	1/4	3/8	20pcs/ctn/21/0.73'
ST-7769(M)	1/4	6	0.4	24,000	1.1	0.5	7.0	179	13	380	1/4	5/16	10pcs/ctn/11/0.92'
ST-7433(M)	1/4	6	0.9	14,600	3.7	1.68	15.35	390	19	540	3/8	3/8	10Pcs/Ctn/19/0.8'
ST-7433G(M)	1/4	6	0.9	14,600	2.86	1.3	13.58	345	19	540	3/8	3/8	10Pcs/Ctn/15/0.6'
ST-7432(M)-4	1/4	6	0.3	23,000	2.14	0.97	11.61	295	13	380	1/4	3/8	10Pcs/Ctn/19/0.8'
ST-7432G(M)-4	1/4	6	0.3	23,000	2.00	0.91	11.81	300	13	380	1/4	3/8	10Pcs/Ctn/19/0.8'



Professional & Industrial Air Grinder



Industrial
ST-10G 3mm
ST-10GS 1/8"
Air Industrial Grinder
(Roll Type)



Industrial
ST-10L 3mm
ST-10LS 1/8"
Air Industrial Grinder
(Lever Type)



Industrial
ST-20G 6mm
ST-20GS 1/4"
Air Industrial Grinder
(Roll Type)
(option:3mm)



Industrial
ST-20L 6mm
ST-20LS 1/4"
Air Industrial Grinder
(Lever Type)
(option:3mm)



Industrial
ST-38G 6mm
ST-38GS 1/4"
ST-38GF 6mm (Front Exhaust)
ST-38GFS 1/4" (Front Exhaust)
Air Industrial Grinder
(Roll Type)



Industrial
ST-38L 6mm
ST-38LS 1/4"
ST-38LF 6mm (Front Exhaust)
ST-38LFS 1/4" (Front Exhaust)
Air Industrial Grinder
(Lever Type)



Industrial
ST-38GE 6mm
ST-38GES 1/4"
Air Extension
Industrial Grinder
(Roll Type)



Industrial
ST-38LE 6mm
ST-38LES 1/4"
Air Extension
Industrial Grinder
(Lever Type)



Industrial
ST-7764HRE 1/4"
ST-7764MHRE 6mm
Air Pro. Grinder
W/Hose
- 0.5HP



Industrial
ST-7765HRE 1/4"
ST-7765MHRE 6mm
Air Pro. Angle Grinder
W/Hose
- 0.3HP



Composite Housing
NEW
ST-C735 1/4"
ST-C735-1 1/8"
ST-C735M 6mm
ST-C735M-3 3mm
Air Die Grinder
- 0.4HP



Composite Housing
NEW
ST-C736 1/4"
ST-C736-1 1/8"
ST-C736M 6mm
ST-C736M-3 3mm
Air Die Grinder
- 0.4HP



Composite Housing
NEW
ST-C737 1/4"
ST-C737-1 1/8"
ST-C737M 6mm
ST-C737M-3 3mm
ST-C737M-8 8mm
Air Die Grinder
- 0.6HP

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Motor (HP)	Carbide bur (mm)	Diamond Pin (mm)	Free speed (r.p.m)	Weight		Length		Dia		Air Inlet (PT)	Air hose (I.D.)	Packing Pcs/ctn/w.g./cuft (kgs)
					Lb	kgs	in	mm	in	mm			
ST-10G(S)	0.1	5	8	60,000	0.2	0.1	6 -1/4	160	5/8	17	1/8"	1/4"	20Pcs/ctn/4/1'
ST-10L(S)	0.1	5	8	60,000	0.2	0.1	6 -1/4	160	5/8	17	1/8"	1/4"	20Pcs/ctn/4/1'
ST-20G(S)	0.2	10	15	40,000	0.8	0.38	6 -1/2	165	1-1/8	28	1/8"	1/4"	20Pcs/ctn/10/1'
ST-20L(S)	0.2	10	15	40,000	0.8	0.38	6 -1/2	165	1-1/8	28	1/8"	1/4"	20Pcs/ctn/10/1'
ST-38G(S)	0.38	20	30	18,000	1.3	0.6	7	178	1-1/4	32	1/8"	1/4"	20Pcs/ctn/14/1'
ST-38GF(S)	0.38	20	30	18,000	1.3	0.6	7	178	1-1/4	32	1/8"	1/4"	20Pcs/ctn/14/1'
ST-38L(S)	0.38	20	30	18,000	1.3	0.6	6 -5/8	172	1-1/4	32	1/8"	1/4"	20Pcs/ctn/14/1'
ST-38LF(S)	0.38	20	30	18,000	1.3	0.6	6 -5/8	172	1-1/4	32	1/8"	1/4"	20Pcs/ctn/14/1'
ST-38GE(S)	0.38	20	30	18,000	1.8	0.8	11-1/4	295	1-1/4	32	1/8"	1/4"	20Pcs/ctn/18/1'
ST-38LE(S)	0.38	20	30	18,000	1.8	0.8	11-3/8	290	1-1/4	32	1/8"	1/4"	20Pcs/ctn/18/1'
ST-7764(M)HRE	0.65	6	-	22,000	2.03	0.92	5.23	205	1-1/2	39	1/4"	3/8"	10Pcs/Ctn/16/1.5'
ST-7765(M)HRE	0.30	6	-	19,000	1.2	0.55	6.5x2.6	165x68	1-1/5	31	1/4"	3/8"	20Pcs/Ctn/21.5/2.8'
ST-C735(M)	0.40	-	-	25,000	0.46	1.01	7	179	1-1/3	36	1/4"	3/8"	20Pcs/Ctn/13/0.73'
ST-C736(M)	0.40	-	-	20,000	0.62	1.36	7-1/5	182	1-1/3	36	1/4"	3/8"	20Pcs/Ctn/15.7/0.73'
ST-C737(M)	0.60	-	-	20,000	0.71	1.56	7-4/5	198	1-2/3	42	1/4"	3/8"	20Pcs/Ctn/18.8/1.1'



Air Die Grinder



ST-7494 1/4"
ST-7494M 6mm
Professional Air Angle Die Grinder
Speed: 18,000 rpm
- 0.75HP



ST-7495 1/4"
ST-7495M 6mm
Professional Air Die Grinder
Speed: 24,000 rpm
- 0.75HP



ST-7495L 1/4"
ST-7495LM 6mm
Professional 3.5" Air Extension Die Grinder
Speed: 22,800 rpm
- 1HP



ST-7495L-5 1/4"
ST-7495LM-5 6mm
Professional 5.5" Air Extension Die Grinder
Speed: 22,700 rpm
- 1HP



ST-7495L-12 1/4"
ST-7495LM-12 6mm
Professional 12" Air Extension Die Grinder
Speed: 22,100 rpm
- 1HP



ST-7495L-20 1/4"
ST-7495LM-20 6mm
Professional 20" Air Extension Die Grinder
Speed: 22,300 rpm
- 1HP



ST-P7732 1/4"
ST-P7732M 6mm
Mini Air Die Grinder
Speed: 25,000 rpm



ST-P7733 1/4"
ST-P7733M 6mm
Air Die Grinder
Speed: 22,000 rpm



ST-P7733L-3 1/4"
ST-P7733LM-3 6mm
3" Extension Air Die Grinder
Speed: 22,000 rpm



ST-P7733L 1/4"
ST-P7733LM 6mm
5" Extension Air Die Grinder
Speed: 22,000 rpm



ST-P7733A 1/4"
ST-P7733AM 6mm
Low Speed Air Die Grinder
Speed: 3,600 rpm



ST-P7734 1/4"
ST-P7734M 6mm
Mini Air Angle Die Grinder
Speed: 20,000 rpm



ST-P7735 1/4"
ST-P7735M 6mm
Air Angle Die Grinder
Speed: 18,000 rpm



GS-10
10 Pcs Grinder Stones Set

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Collet Size		Air Inlet (PT)	Air Hose (I.D.)		Air Consumption		Overall Length		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		in	mm		in	mm	cfm	l/min	in	mm	lbs	kgs	
ST-7494(M)	18,000	1/4	6	1/4"	3/8	10	13	380	6-9/10	175	1.8	0.80	12/Ctn/11/0.8'
ST-7495(M)	24,000	1/4	6	1/4"	3/8	10	13	380	6-9/10	175	0.14	0.65	12/Ctn/11/0.8'
ST-7495L(M)	22,800	1/4	6	1/4"	3/8	10	13	380	9-9/20	240	1.7	0.77	12/Ctn/13/1.1'
ST-7495L(M)-5	22,700	1/4	6	1/4"	3/8	10	13	380	10-19/20	278	1.9	0.85	10/Ctn/14/1.5'
ST-7495L(M)-12	22,100	1/4	6	1/4"	3/8	10	13	380	17-9/10	455	2.9	1.30	10/Ctn/15/2'
ST-7495L(M)-20	22,300	1/4	6	1/4"	3/8	10	13	380	25-4/5	655	3.9	1.75	8/Ctn/18/2'
ST-P7732(M)	25,000	1/4	6	1/4"	3/8	10	13	380	6-1/10	155	0.9	0.43	12/Ctn/11/0.8'
ST-P7733(M)	22,000	1/4	6	1/4"	3/8	10	13	380	6-9/10	176	1.3	0.60	12/Ctn/11/0.8'
ST-P7733A(M)	3,600	1/4	6	1/4"	3/8	10	13	380	7-4/5	200	1.5	0.70	12/Ctn/13/1.1'
ST-P7733L(M)-3	22,000	1/4	6	1/4"	3/8	10	13	380	9-2/5	240	1.5	0.70	12/Ctn/13/1.1'
ST-P7733L(M)	22,000	1/4	6	1/4"	3/8	10	13	380	11-1/10	280	1.8	0.83	10/Ctn/10/0.96'
ST-P7734(M)	20,000	1/4	6	1/4"	3/8	10	13	380	6-1/10	155	1.1	0.53	12/Ctn/11/0.8'
ST-P7735(M)	18,000	1/4	6	1/4"	3/8	10	13	380	7	178	1.7	0.77	12/Ctn/11/0.8'



Air Die Grinder



ST-7732F 1/4"
ST-7732FM 6mm
 Mini Air Die Grinder
 (Front Exhaust)
 Speed: 25,000 rpm



ST-7733F 1/4"
ST-7733FM 6mm
 Air Die Grinder
 (Front Exhaust)
 Speed: 20,000 rpm



ST-7734F 1/4"
ST-7734FM 6mm
 Air Angle Die Grinder
 (Front Exhaust)
 Speed: 18,000 rpm

ST-P7733(M)K

Air Die Grinder Kit
 Contents:
 1-ST-P7733(M)
 2-Spanners
 5-1/4" (or 6mm) Shank Grinding Stones
 5-1/8" (or 3mm) Shank Grinding Stones
 1-1/8" (or 3mm) Collet
 1-Nipple
 1-Blow Case



ST-7732 1/4"
ST-7732M 6mm
 Mini Air Die Grinder
 Speed: 25,000 rpm



ST-7733 1/4"
ST-7733M 6mm
 Air Die Grinder
 Speed: 22,000 rpm

ST-P7734(M)K

Mini Air Angle Die Grinder Kit
 Contents:
 1-ST-P7734 or ST-P7734M
 1-2" Roloc Pad
 5-2" Roloc Scotch Discs
 1-1/8" (or 3mm) Collet
 5-1/8" (or 3mm) Shank Grinding Stones
 5-1/4" (or 6mm) Shank Grinding Stones
 1-Nipple 2-Spanners 1-Blow Case



ST-7734 1/4"
ST-7734M 6mm
 Air Angle Die Grinder
 Speed: 20,000 rpm



ST-7733L 1/4"
ST-7733LM 6mm
 Air Extended Die Grinder
 Speed: 25,000 rpm

ST-P7735(M)K

Air Angle Die Grinder Kit
 Contents:
 1-ST-P7735 or ST-P7735M
 5-1/8" (or 3mm) Shank Grinding Stones
 5-1/4" (or 6mm) Shank Grinding Stones
 5-2" Roloc Scotch Discs
 5-3" Roloc Scotch Discs
 1-1/8" (or 3mm) collet
 1-Nipple 2-Spanners
 2-Roloc Pad, 2-Bolts 1-Blow Case



ST-7732K 1/4"
ST-7732MK 6mm
 Mini Air Die Grinder Kit

Contents:
 1- ST-7732 or ST-7732M
 5- 3mm or 1/8" mounted grinding stones
 5- 6mm or 1/4" mounted grinding stones
 2- hand wrenches
 1- 3mm or 1/8" collet
 1- blow mold case



ST-7733K 1/4"
ST-7733MK 6mm
 Air Die Grinder Kit

Contents:
 1- ST-7733 or ST-7733M
 5- 3mm or 1/8" mounted grinding stones
 5- 6mm or 1/4" mounted grinding stones
 2- hand wrenches
 1- 3mm or 1/8" collet
 1- blow mold case



Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Collet		Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Avg Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		in	mm	in	mm			cfm	l/min	lbs	kgs	
ST-7732F(FM)	25,000	1/4	6	4-3/4	120	1/4"	3/8"	13	380	0.6	0.3	25/Ctn/14/0.75'
ST-7733F(FM)	20,000	1/4	6	5-3/4	146	1/4"	3/8"	13	380	1.17	0.53	25/Ctn/20/0.8'
ST-7734F(FM)	18,000	1/4	6	4-7/8	124	1/4"	3/8"	13	380	0.9	0.40	25/Ctn/19/0.75'
ST-7732(M)	25,000	1/4	6	6-3/16	157	1/4"	3/8"	13	380	0.6	0.3	25Pcs/Ctn/21.7/0.8'
ST-7733(M)	22,000	1/4	6	6-9/11	173	1/4"	3/8"	13	380	2	0.9	20Pcs/Ctn/13/0.7'
ST-7734(M)	20,000	1/4	6	5-3/4	146	1/4"	3/8"	13	380	1.08	0.49	25Pcs/Ctn/19/0.75'
ST-7733L(M)	25,000	1/4	6	10-1/4	260	1/4"	3/8"	13	380	1.41	0.64	20Pcs/Ctn/16/0.9'

Air Micro Grinder & Engraving Pen



ST-909
Engraving Pen
(3,500~3,800b.p.m.)



ST-909A
Engraving Pen
(30,000~34,000b.p.m.)



ST-6501
Engraving Pen
(3,300~3,400b.p.m.)



ST-3370 1/8"
ST-3370M 3mm
Air Micro Grinder
(56,000r.p.m.)



ST-3371 1/8"
ST-3371M 3mm
Air Micro Grinder With PU Grip
(60,000 r.p.m.)



NEW
ST-3372 1/8"
ST-3372M 3mm
Air Micro Die Grinder
(60,000r.p.m.)



NEW
ST-3373 1/8"
ST-3373M 3mm
Heavy Duty Air Micro Grinder
(60,000r.p.m.)



NEW
ST-3375 1/8"
ST-3375M 3mm
Air Micro Grinder
(60,000r.p.m.)



NEW
ST-3391
90° Air Micro Grinder
(21,000r.p.m.)



NEW
ST-3392
120° Air Micro Grinder
(21,000r.p.m.)



ST-3380 1/8" **Industrial**
ST-3380M 3mm
Micro Air Grinder (70,000r.p.m.)



ST-3360A 1/8" **Industrial**
ST-3360MA 3mm
Micro Air Grinder (35,000r.p.m.)



ST-3390 **Industrial**
30mm Minil Angle
Grinder/Sander
(22,000 r.p.m.)

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Capacity		Overall Length		Air Inlet (PT)	Air Hose (I.D.)	Air Consumption		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
		in	mm	in	mm			cfm	l/min	lbs	kgs	
ST-909	3,500~3,800	-	-	6-3/4	170	1/4"	3/8"	6	170	0.42	0.9	30Pcs/Ctn/9.3/1.7'
ST-909A	30,000~34,000	-	-	6-2/5	160	1/4"	3/8"	6	170	0.5	0.2	20Pcs/Ctn/13/1.87'
ST-6501	3,300~3,400	-	-	5-2/5	137	1/4"	3/8"	6	170	0.25	0.11	30Pcs/Ctn/12/1.6'
ST-3370(M)	56,000	1/8	3	5-1/4	132	1/4"	3/8"	6	170	0.5	0.2	20Pcs/Ctn/9/1.13'
ST-3371(M)	60,000	1/8	3	5-1/5	132	1/4"	3/8"	6	170	0.287	0.13	30Pcs/Ctn/14/1.31'
ST-3372(M)	60,000	1/8	3	5-9/20	130	1/4"	3/8"	6	170	0.55	0.22	20Pcs/Ctn/8/1.2'
ST-3373	60,000	1/8	3	5-3/5	140	1/4"	3/8"	6	170	0.6	0.24	20Pcs/Ctn/8/1.2'
ST-3375(M)	60,000	1/8	3	5-9/20	130	1/4"	3/8"	6	170	0.55	0.22	20Pcs/Ctn/8/1.2'
ST-3391	21,000	1-3/10	30	6-2/5	160	1/4"	3/8"	6	170	0.5	0.2	20Pcs/Ctn/9/1.13'
ST-3392	21,000	1-3/10	30	6-2/5	160	1/4"	3/8"	6	170	0.287	0.13	30Pcs/Ctn/14/1.31'
ST-3380(M)	70,000	1/8	3	5-1/4	132	1/4"	3/8"	6	170	0.8	0.4	30Pcs/Ctn/22/1.8'
ST-3360(M)A	35,000	1/8	3	6-9/10	175	1/4"	5mm	6	170	0.77	0.35	20Pcs/Ctn/11/1'
ST-3390	22,000	1-3/16	30	5-1/3	136	1/4"	3/8"	6	170	0.6	0.3	20Pcs/Ctn/10/2'