

# Du-Pas®

ISO-9001 CERTIFICATED

**Cordless Shut-off Screwdriver**

## INDUSTRIAL POWER TOOLS

### SCT Series Brushless Motor



- Torque adjustment.
- LED light for working in dark area.
- Trigger repeat protection avoid double hits on already seated screw.
- LED indicator provides simple process information to the operator. The signal is visible from any angle.
- Press button for easy F/R operation.
- Ergonomical handle design provides a well-balance.
- Easy attached sliding battery system.
- Li-ion battery pack delivers longer run-time.

#### Mini USB Connector:

Tool speed can be adjusted by additional programmer.

LED indicator provides simple process information to the operator. The signal is visible from any angle.



Blue light indicates that the tool is in reverse operation.



Green light indicates that the preset torque is reached and tightening is completed.



Red light with a long "beep" sound indicates that the tightening was failed.



Yellow light with a "beep" sound indicates that the battery is dead. Must change the battery pack immediately.



Yellow Flashing light with five short beep sounds indicates low battery.

#### SPECIFICATIONS Adjustment screwdriver , spanner are included with the tool.

| Model  | Volt. | Drive Size | Screw Size | Weight w/o Batt. |     | Vibration Value  | Noise Level | Free Speed | Torque Range (N.m) |            |
|--------|-------|------------|------------|------------------|-----|------------------|-------------|------------|--------------------|------------|
|        | V     | in         | mm         | kg               | lb  | m/s <sup>2</sup> | dB(A)       | rpm        | Hard joint         | Soft joint |
| SCT-3  | 18    | 1/4" Hex.  | M3~M4      | 0.95             | 2.1 | <2.5             | <75         | 500~1,550  | 0.8~3              | 0.8~3      |
| SCT-6  | 18    | 1/4" Hex.  | M3~M5      | 0.95             | 2.1 | <2.5             | <75         | 300~1,000  | 1~6                | 1~6        |
| SCT-9  | 18    | 1/4" Hex.  | M3~M5      | 0.95             | 2.1 | <2.5             | <75         | 300~800    | 1.5~9              | 1.5~9      |
| SCT-12 | 18    | 1/4" Hex.  | M4~M6      | 0.95             | 2.1 | <2.5             | <75         | 250~600    | 2~12               | 2~12       |