



Industrial Air Angle Grinder

Features:

- ★ The cylinder is durable and longer lifespan.
- ★ Increase gear strength, consequently the abrasive life is improved.



Industrial
ST-7435 1/4"
ST-7435M 6mm
(Lever Type)
0.4HP



Industrial
ST-7435G 1/4"
ST-7435GM 6mm
(Rotary Type)
0.4HP



Industrial
ST-7435A 1/4"
ST-7435AM 6mm
(Lever Type)
0.4HP



Industrial
ST-7435AG 1/4"
ST-7435AGM 6mm
(Rotary Type)
0.4HP



Industrial
ST-7830L 2"
(Lever Type)
0.4HP



ST-7830G 2"
(Rotary Type)
0.4HP



ST-7834L 4"
(Lever Type)
0.7HP



ST-7834G 4"
(Rotary Type)
0.7HP



Industrial
ST-7844L 4"
ST-7845L 5"
(Lever Type)
1HP



ST-7844G 4"
ST-7845G 5"
(Rotary Type)
1HP



Industrial
ST-7871L-A 7"
spindle:5/8"x11UNF
ST-7871L-B 7"
spindle:1/2"x16
(Lever Type)
1.3HP



ST-7871G-A 7"
spindle:5/8"x11UNF
ST-7871G-B 7"
spindle:1/2"x16
(Rotary Type)
1.3HP



ST-7890L 9"
(Lever Type)
2.5HP



ST-7890G 9"
(Rotary Type)
2.5HP



ST-7436
3" Straight Grinder
(Lever Type)
0.9HP



ST-7436G
3" Straight Grinder
(Rotary Type)
0.9HP

Specification:

Recommend Air Pressure: 6.3 kg/cm² (90psi)

Model No.	Free Speed (r.p.m.)	Disc Size (inch)	Spindle Size (Dia. x thread)	Air Inlet (PT)	Air Hose (I.D.)	Avg Air Consumption		Overall Length		Net Weight		Packing Pcs/Ctn/G.W./Cuft (kgs)
						cfm	l/min	in	mm	lbs	kgs	
ST-7435(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.54	166	1.65	0.75	20Pcs/Ctn/18/0.9'
ST-7435G(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.26	159	1.41	0.64	20Pcs/Ctn/15/0.8'
ST-7435A(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.54	166	1.68	0.76	20Pcs/Ctn/18/0.9'
ST-7435AG(M)	15,000	-	1/4"(bpm)Collet	1/4	3/8	13	380	6.26	159	1.43	0.65	20Pcs/Ctn/15/0.8'
ST-7830L	15,000	2	1/4"-28UNF	1/4	3/8	13	380	6.61	168	1.68	0.76	20Pcs/Ctn/18/0.9'
ST-7830G	15,000	2	1/4"-28UNF	1/4	3/8	13	380	6.22	158	1.41	0.64	20Pcs/Ctn/15/0.8'
ST-7834L	15,000	4	M8x1.0	1/4	3/8	19	540	7.28	185	2.53	1.15	10Pcs/Ctn/13/1.1'
ST-7834G	15,000	4	M8x1.0	1/4	3/8	19	540	7.28	185	2.53	1.15	10Pcs/Ctn/13/1.1'
ST-7844L	13,500	4	M8x1.25	1/4	3/8	19	540	10.63	270	4.44	2.02	10Pcs/Ctn/21/1.5'
ST-7844G	13,500	4	M8x1.25	1/4	3/8	19	540	8.59	218	3.83	1.74	10Pcs/Ctn/19/1.3'
ST-7845L	13,500	5	M14x2.0	1/4	3/8	19	540	10.63	270	4.44	2.02	10Pcs/Ctn/21/1.5'
ST-7845G	13,500	5	M14x2.0	1/4	3/8	19	540	8.59	218	3.83	1.74	10Pcs/Ctn/19/1.3'
ST-7871L-A	7,000	7	5/8"-11UNF	3/8	3/8	29	820	10.71	272	5.59	2.54	6Pcs/Ctn/19/1.6'
ST-7871L-B	7,000	7	1/2"-16	3/8	3/8	29	820	10.75	273	5.28	2.4	6Pcs/Ctn/19/1.6'
ST-7871G-A	7,000	7	5/8"-11UNF	3/8	3/8	29	820	10.04	255	5.9	2.68	6Pcs/Ctn/19/1.6'
ST-7871G-B	7,000	7	1/2"-16	3/8	3/8	29	820	10.04	255	5.9	2.68	6Pcs/Ctn/19/1.6'
ST-7890L	5,900	9	1/2"-16	1/2	3/8	40	1130	13.78	350	9.68	4.4	4Pcs/Ctn/22/1.4'
ST-7890G	5,900	9	1/2"-16	1/2	3/8	40	1130	12.17	309	9.68	4.4	4Pcs/Ctn/22/1.4'
ST-7436	14,600	-	3/8"-16	3/8	3/8	20	566	15.35	390	3.78	1.72	10Pcs/Ctn/15/0.6'
ST-7436G	14,600	-	3/8"-16	3/8	3/8	20	566	13.58	345	2.86	1.3	10Pcs/Ctn/15/0.6'